

PROFESSIONAL LIFTING EQUIPMENT



**HEIN-WERNER
AUTOMOTIVE®**



**Porto-Power.
BLACKHAWK AUTOMOTIVE**



4 TON PORTO-POWER KIT

B65114

4 Ton Porto-Power Kit

4-ton capacity model gives you the pushing and spreading power you need to make fast and easy work of everyday repairs.

- Snap-lock design for quick, easy assembly
- Automatic pump overload system protects against damage to rams and equipment
- 4 ton kit comes in a blow molded plastic case
- Heavy walled extension tubes stand up in tough applications
- Flex head features permanently molded rubber pad—interlocked to prevent separation
- Long handles provide low pumping effort
- 1/2 ton capacity hydraulic spreader features 2" jaws and spreads from 5/8" to 3-3/4"




| Model | Ram Capacity | Pump Capacity | Ram | | Ram Effective Area | G.W. |
|---------------|--------------|---------------|---------------|-----------------|---------------------|---------|
| | | | Closed Height | Extended Height | | |
| B65114 | 4 Ton | 8,000 PSI | 11" | 15-3/4" | 1.0 in ² | 46 Lbs. |

10 TON PORTO-POWER KIT

B65115 10 Ton Porto-Power Kit

The 10 ton capacity model gives you the extra muscle you need to get the job done right.

- Snap-lock design for quick, easy assembly
- Automatic pump overload system protects against damage to rams and equipment
- Heavy walled extension tubes stand up in tough applications
- Flex head features permanently molded rubber pad-interlocked to prevent separation
- Long handles provide low pumping effort
- 1/2 ton capacity hydraulic spreader features 2" jaws and spreads from 5/8" to 3-3/4"
- Custom fitted, rugged blow molded storage case with wheels for easy movement between jobs



- | | | |
|-----------------------------------|--------------------------------|--------------------------------------|
| A. B65068 • Mobile Case | H. B65172 • Plunger Toe | O. B65163 • 18" Extension Tube |
| B. B65188 • 10 Ton Hydraulic Pump | I. B65123 • 1/2 Ton Spreader | P. B65164 • 10" Extension Tube |
| C. B65189 • 10 Ton Hydraulic Ram | J. B65167 • Serrated Saddle | Q. B65165 • 4" Extension Tube |
| D. B65291 • 6' Hose w/ Coupler | K. B65173 • 90° V Base | U. B69477 • Female Coupler, 1/4" NPT |
| E. B65179 • Male Connector | L. B65169 • Ram Toe | V. B69478 • Male Coupler, 1/4" NPT |
| F. B65168 • Flat Base | M. B65166 • Wedge Head | |
| G. B65180 • Rubber Head | N. B65162 • 27" Extension Tube | |

| Model | Ram Capacity | Pump Capacity | Ram | | Ram Effective Area | G.W. |
|---------------|--------------|---------------|---------------|-----------------|---------------------|---------|
| | | | Closed Height | Extended Height | | |
| B65115 | 10 Ton | 10,000 PSI | 13-5/8" | 19-3/4" | 2.4 in ² | 88 Lbs. |

20 TON PORTO-POWER KIT

B65041

20 Ton Porto-Power Kit

20 Ton Porto-Power set provides extra capacity for the toughest assignments. Two-speed pump extends ram quickly saving time and money.

Versatile attachments provide broad range of function. Automatic two speed pump speeds ram to load, then shifts power stroke. With this set, spread materials apart and pull heavy duty machinery and sections. This is a heavy duty set makes all bull-work repairs easier.



- | | | |
|--------------------------------|------------------------------------|--------------------------------------|
| A. B65073 • Wood Chest | H. B65770 • Connector | O. B65740 • 20 Ton Ram |
| B. B65775 • Chain Pull Plate | I. B65772 • V Head | P. B65593 • 6' Hydraulic Hose |
| C. B65768 • 24" Extension Tube | J. B65776 • Threaded Coupling (3) | Q. B65774 • Lifting Toe |
| D. B65766 • 18" Extension Tube | K. B65421 • 2 Speed Automatic Pump | R. B65779 • Plunger Base |
| E. B65764 • 10" Extension Tube | L. B97518 • 8' Chain w/ hook | S. B65778 • Ram Base |
| F. B65762 • 5" Extension Tube | M. B65773 • Wedge Head | T. B65581 • Male Coupler, 3/8" NPT |
| G. B65760 • 3" Extension Tube | N. B65771 • Saddle (2) | U. B65582 • Female Coupler, 3/8" NPT |

| Model | Ram Capacity | Ram | | Ram Effective Area | G.W. |
|---------------|--------------|---------------|-----------------|----------------------|----------|
| | | Closed Height | Extended Height | | |
| B65041 | 20 Ton | 10-13/16" | 16-3/4" | 5.14 in ² | 206 Lbs. |

HYDRAULIC HAND PUMPS

B65122

Hydraulic Hand Pump

&

B65421

Hydraulic Hand Pump

- Lightweight and compact design
- Aluminum pump head for maximum corrosion resistance
- Two speed operation reduces handle strokes by as much as 78% over single speed pumps
- Lower handle effort to minimize operator fatigue
- Handle lock and lightweight construction for easy carrying
- Internal pressure relief valve for overload protection



B65421

B65122

| Model | Capacity | Output Displacement Per Stroke | | Operating Force | Piston Stroke | Oil Outlet Port | G.W. (with fluid) |
|---------------|----------------------|--------------------------------|-----------------------|-----------------|---------------|-----------------|-------------------|
| | | 1 st Stage | 2 nd Stage | | | | |
| B65122 | 21.4 in ³ | 0.18 in ³ | 0.05 in ³ | 88 Lbs. | 0.98" | 1/4"-18NPTF | 7 Lbs. |
| B65421 | 61 in ³ | 0.81 in ³ | 0.14 in ³ | 132 Lbs. | 0.82" | 3/8"-18NPTF | 13 Lbs. |

FLAT BODY RAMS

B65139

5 Ton Flat Body Kit

- 5 Ton flat body kit includes a blow mold case and 4 adapters (0.25", 0.5", 1" and 1.25")
- Magnetic adapters are stackable U.S. Patent No.7,237,762 b2

B65140

4 Ton Flat Body Ram



B65139



B65140



| Model | Capacity | Stroke | Effective Area | Oil Capacity | Collapsed Height | Extended Height | Outside Dimension | Plunger Diameter | Base To Intel Port | Base Mounting Hole | | G.W. | Operating Pressure | Coupler |
|---------------|----------|--------|---------------------|----------------------|------------------|-----------------|-------------------|------------------|--------------------|--------------------|---------------|--------|--------------------|---------|
| | | | | | | | | | | Hole Diameter | Hole Distance | | | |
| B65140 | 4 Ton | 0.63" | 1.1 in ² | 0.69 in ³ | 1.63" | 2.26" | 2.26" X 1.58" | 0.98" | 0.74" | 0.2" | 1.1" | 2 Lbs. | 8,050 PSI | B69477 |
| B65139 | 5 Ton | 0.24" | | 0.26 in ³ | 1.26" | 1.5" | | | 0.80" | | | 6 Lbs. | 9,100 PSI | |

AIR HYDRAULIC FOOT PUMPS

B65425

10,000 PSI Air Foot Operated Pump

- Maximum working pressure 10,000 PSI
 - High strength aluminum reservoir is lightweight and corrosion resistant
 - Suggested air pressure 110-175 PSI
 - Pressure relief valve for overload protection
 - Three-positions provide cylinder advance, hold, or retract operation
 - A compact yet powerful Air Turbo Motor is equipped to raise the load to the desired height efficiently, effortlessly, and safely
- U.S. Patent No. 5,341,723

Use
Standard Shop Air!
[110-175 PSI pressure]



B65425

B65426

10,000 PSI Air Foot Operated Pump

- Rugged construction built for long life and easy operation
 - Swivel coupling simplifies hydraulic connection and pump operation
 - Three-positions provide cylinder advance, hold, or retract operation
 - Operates in any position
 - Base mounting plate included
 - A compact yet powerful Air Turbo Motor is equipped to raise the load to the desired height efficiently, effortlessly, and safely
- U.S. Patent No. 5,341,723



Use
Standard Shop Air!
[110-175 PSI pressure]

B65426

B65427

10,000 PSI Air Foot Operated Pump

- Greater oil capacity to handle bigger jobs
 - Maximum working pressure 10,000 PSI
 - High strength aluminum reservoir is lightweight and corrosion resistant
 - Suggested air pressure 110-175 PSI
 - Pressure relief valve for overload protection
 - Three-positions provide cylinder advance, hold, or retract operation
 - A compact yet powerful Air Turbo Motor is equipped to raise the load to the desired height efficiently, effortlessly, and safely
- U.S. Patent No. 5,341,723

Use
Standard Shop Air!
[110-175 PSI pressure]



B65427

| Model Number | Usable Capacity | Rated pressure | Output Flow Rate (in3/min.) | | Input Air Pressure | Output Port Threads | Input Port Threads | G.W. (with fluid) |
|--------------|----------------------|----------------|-----------------------------|------|--------------------|---------------------|--------------------|-------------------|
| | | | No Load | Load | | | | |
| B65425 | 91.5 in ³ | 10,000 PSI | 66 | 11 | 110-175 PSI | 3/8"-18NPTF | 1/4"-18 NPT | 18 Lbs. |
| B65426 | 36.6 in ³ | | 61 | 9 | | | | 15 Lbs. |
| B65427 | 122 in ³ | | 65 | 12 | | | | 20 Lbs. |

HYDRAULIC SETS



B65407

Use
Standard Shop Air!
[110-175 PSI pressure]

B65407 Hydraulic Set

- Combo includes B65426, B65593 and B65444
- Rugged construction – built for long life and easy operation
- Swivel coupling simplifies hydraulic connection and pump operation
- Three-positions provide cylinder advance, hold, or retract operation
- Operates in any position
- Base mounting plate included



B65428

Use
Standard Shop Air!
[110-175 PSI pressure]

B65428 Air Hydraulic Pump & Hose Combo

- Combo includes B65426 and B65293
- Rugged construction – built for long life and easy operation
- Swivel coupling simplifies hydraulic connection and pump operation
- Three-positions provide cylinder advance, hold, or retract operation
- Operates in any position
- Base mounting plate included

SPREADER



B65145

B65145 1 Ton Spreader

- Includes a B69477 Coupler
- Designed to work in confined working space
- Can be used with B65114 or B65115

| Model | Capacity | Stroke | Cylinder Effective Area | Ram Collapsed Height | Ram Extended Height | G.W. |
|---------------|----------|--------|-------------------------|----------------------|---------------------|--------|
| B65145 | 1 Ton | 3.79" | 1.09 in ² | 0.47" | 3.9" | 5 Lbs. |

HYDRAULIC RAMS

- Designed for use in all positions
- High strength alloy steel for durability
- Heavy duty return springs (except B65141)
- Baked enamel finish for increased corrosion resistance
- Collar thread protectors (except B65141)
- Rod wipers seal out contaminants
- Industrial hard chrome plated ram prevents rust corrosion



B65141 B65441 B65553 B65555 B65446 B65746 B65449

Porto Power Rams

| Model | Capacity | Stroke | Effective Area | Oil Capacity | Collapsed Height | Extended Height | Outside Diameter | Plunger Diameter | Base To Intel Port | Base Hole Depth | G.W. | Operating Pressure | Coupler |
|--------|----------|--------|----------------------|-----------------------|------------------|-----------------|------------------|------------------|--------------------|-----------------|---------|--------------------|---------|
| B65150 | 4 Ton | 5.0" | 1.0 in ² | 5.00 in ³ | 10.69" | 15.69" | 1.50" | 0.88" | 1.96" | 1.54" | 5 Lbs. | 8,000 PSI | B69477 |
| B65452 | 10 Ton | 6.03" | 2.24 in ² | 13.44 in ³ | 14.59" | 20.62" | 2.26" | 1.50" | 3.15" | 2.42" | 12 Lbs. | 8,950 PSI | B65582 |

Threaded Rams

- High quality threaded single acting cylinders
- Used to attach accessories to rod end and base

| Model | Capacity | Stroke | Effective Area | Oil Capacity | Collapsed Height | Extended Height | Outside Diameter | Plunger Diameter | Base To Intel Port | Plunger Outside Thread & Base Internal Thread | G.W. | Operating Pressure |
|--------|----------|--------|----------------------|-----------------------|------------------|-----------------|------------------|------------------|--------------------|---|---------|--------------------|
| B65142 | 4 Ton | 5.07" | 1.0 in ² | 5.00 in ³ | 10.31" | 15.39" | 1.50" | 1.0" | 1.33" | 3/4"-14 NPTF | 5 Lbs. | 8,000 PSI |
| B65442 | 10 Ton | 6.1" | 2.24 in ² | 13.44 in ³ | 11.61" | 17.72" | 2.27" | 1.5" | 1.67" | 1-1/4"-11.5 NPTF | 11 Lbs. | 8,930 PSI |
| B65444 | | 10.12" | | 22.40 in ³ | 15.63" | 25.75" | | | | | | |
| B65740 | 20 Ton | 5.16" | 5.14 in ² | 25.70 in ³ | 11.77" | 16.93" | 3.35" | 2.24" | 1.85" | 2"-11.5 NPTF | 22 Lbs. | 7,780 PSI |

Regular Rams

| Model | Capacity | Stroke | Effective Area |
|--------|----------|--------|----------------------|
| B65141 | 2 Ton | 3.07" | 0.76 in ² |
| B65553 | 5 Ton | 3.07" | 1.0 in ² |
| B65555 | | 5.08" | |
| B65441 | 10 Ton | 2.01" | 2.24 in ² |
| B65446 | | 5.94 | |
| B65449 | 25 Ton | 9.96" | 5.14 in ² |
| B65746 | | 5.94" | |

| Oil Capacity | Collapsed Height | Extended Height | Outside Diameter | Plunger Diameter | Base to Intel Port | Saddle Diameter | Base Mounting Hole | | | G.W. | Operating Pressure | Coupler |
|-----------------------|------------------|-----------------|------------------|------------------|--------------------|-----------------|--------------------|---------------|------------|-----------|--------------------|---------|
| | | | | | | | Hole Diameter | Hole Distance | Hole Depth | | | |
| 2.28 in ³ | 5.39" | 8.46" | 1.31" | 0.87" | 0.46" | 1.0" | N/A | N/A | N/A | 2 Lbs. | 5,270 PSI | |
| 3.00 in ³ | 6.65" | 9.72" | 1.5" | 1.0" | 0.79" | 0.98" | 0.20" | 1.00" | 0.76" | 3.2 Lbs. | 10,000 PSI | B69477 |
| 5.00 in ³ | 8.7" | 13.78" | | | | | | | | 4.1 Lbs. | | |
| 4.48 in ³ | 4.84" | 6.85" | | | | | 0.28" | 1.54" | 0.87" | 4.9 Lbs. | 8,930 PSI | |
| 13.44 in ³ | 9.84" | 15.78" | 2.26" | 1.49" | 0.75" | 1.38" | 0.31" | | 0.55" | 9 Lbs. | B65582 | |
| 22.31 in ³ | 13.86" | 23.82" | | | | | | | 14 Lbs. | | | |
| 30.84 in ³ | 10.71" | 16.81" | 3.35" | 2.24" | 0.98" | 2.13" | 0.4" | 2.3" | 1.0" | 23.1 Lbs. | 9,730 PSI | B65582 |



FRAME STRAIGHTENER

B93601B

10 Ton Capacity Pulling Post Package

- Use with common pot patterns or chainless anchor system
- Longer/wide base for stability
- Safety tie-down brackets
- Utilizes 10" ram for longer pulls

B93601B Includes:

- A. B93600 • Pulling post
- B. B65428 • Pump/hose set
- C. B65444 • 10 Ton 10" stroke ram
- D. B97662 • 6' Chain with claw hooks (2)
- E. B97691 • 9' Chain with hook



B93601B

| Model | Capacity | Height | Base Size | Floating Pulley Position | G.W. |
|---------|----------|--------|-----------|--------------------------|----------|
| B93601B | 10 Ton | 59" | 31" X 16" | 10 | 164 Lbs. |

B93075

Anchor Pot

- Arrange anchor pot in basic pattern or make additional bay installation.
- Designed with heavy-duty protective ring at top which prevents chipping of concrete. 3-1/8" diameter



B93075

PULL RAMS

B65143

**2 Ton Capacity Pull Ram with Hook
&**

B65454

5 Ton Capacity Pull Ram with Hook

- Pull rams are equipped with chain adapter claw hooks on each end
- Accept 3/8" chain links



| Model | Capacity | Stroke | Effective Area | Oil Capacity | Collapsed Height | Extended Height | Outside Diameter | Plunger Diameter | Top To Intel Port | Ram Outside Thread & Base Mounting Hole | G.W. | Operating Pressure | Coupler |
|---------------|----------|--------|----------------------|----------------------|------------------|-----------------|------------------|------------------|-------------------|---|---------|--------------------|---------|
| B65143 | 2 Ton | 5.0" | 0.56 in ² | 2.80 in ³ | 10.51" | 15.51" | 1.89" | 0.75" | 0.74" | 3/4"-14 NPTF | 7 Lbs. | 7,150 PSI | B69477 |
| B65454 | 5 Ton | 5.55" | 1.14 in ² | 6.33 in ³ | 11.93" | 17.48" | 2.25" | 1.18" | 0.80" | 1-1/4"-11.5 NPTF | 10 Lbs. | 8,780 PSI | |

ACCESSORIES

Gauges

B65782 • 4" Wet Gauge 1/4" NPTF
B65783 • 4" Dry Gauge 1/4" NPTF



B65782

B65783

Fittings

B65129 • Reducer from 3/8" to 1/4"
B65131 • 1/4" NPTF Gauge Fitting
B65132 • Bushing from 1/4" to 3/8"



B65129

B65131

B65132

ACCESSORIES

Hydraulic Coupler Set



| Complete Set | Hose Half | Ram Half | Hose/Ram Thread | Coupler Connecting Thread |
|----------------------------|-----------|----------|-----------------|---------------------------|
| Porta-Power Coupler | B69478 | B69477 | 1/4" NPT | 13/16"- 20 UNEF |
| B65280 | B65281 | B65282 | 1/4" NPT | 3/4" - 20 UNEF |
| B65580 | B65581 | B65582 | 3/8" NPT | 15/16"- 20 UNEF |

Hydraulic Hoses

B65290 • 1/4" ID, 6' Hose, 1/4" NPT Connection

B65291 • 1/4" ID, 6' Hose with Male (B69478) Coupler, 1/4" NPT Connection

B65590 • 3/8" ID, 10' Hose with Male (B65580) Coupler, 3/8" NPT Connection

B65591 • 1/4" ID, 10' Hose with Male (B69478) Half Coupler, 1/4" NPT Connection

B65593 • 3/8" ID, 6' Hose with Male (B65580) Half Coupler, 3/8" NPT Connection

B65594 • 3/8" ID, 6' Hose, 3/8" NPT Connection



| Model | Hose Size | Length | Hose End Fitting | Coupler |
|--------|-----------|--------|---------------------|----------------------------|
| B65290 | 1/4" ID | 6' | 1/4" NPT Connection | - |
| B65291 | | | | Male Half Coupler (B69478) |
| B65590 | 3/8" ID | 10' | 3/8" NPT Connection | Male Half Coupler (B65581) |
| B65591 | 1/4" ID | | 1/4" NPT Connection | Male Half Coupler (B69478) |
| B65593 | 3/8" ID | 6' | 3/8" NPT Connection | Male Half Coupler (B65581) |
| B65594 | | | | - |

Chains & Hooks

B97520 • Double grab hook

B97651 • 15' Chain with claw hook

B97661 • 6' Chain with claw hook

B97662 • 6' Chain with 2 claw hooks

B97691 • 9' Chain with grab hook

B97518 • 8' Chain with grab hook

B97521 • Hook assembly

B97527 • 6' Chain with grab hook

B97528 • 6' Chain with 2 grab hooks



WARRANTY



ONE YEAR LIMITED WARRANTY

Warranty Information

For a period of one (1) year from date of purchase, SFA Companies will repair or replace, at its option, without charge, any of its products which fails due to defect in material or workmanship, or which fails to conform to any implied warranty not excluded hereby. Performance of any obligation under this warranty may be obtained by returning the warranted product, freight prepaid, to SFA Companies Warranty Service Department, 10939 N.Pomona Avenue, Kansas City, MO 64153. Except where such limitations and exclusions are specifically prohibited by applicable law.

- (1) THE CONSUMER'S SOLE AND EXCLUSIVE REMEDY SHALL BE THE REPAIR OR REPLACEMENT OF DEFECTIVE PRODUCTS AS DESCRIBED ABOVE.
- (2) SFA COMPANIES SHALL NOT BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGE OR LOSS WHATSOEVER.
- (3) THE DURATION OF ANY AND ALL EXPRESSED AND IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION, ANY WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, IS LIMITED TO A PERIOD OF ONE (1) YEAR FROM DATE OF PURCHASE.

- Some states do not allow limitations on how long an implied warranty lasts, so above limitation may not apply to you.
- Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. The warranty gives you specific legal rights, and you may also have other rights which vary from state to state.



GLOBAL LOCATIONS



USA -
Shinn Fu Company of America
10939 N. Pomona Ave.
Kansas City, MO 64153
USA
Tel: 888.332.6419, 816.891.6390
Fax: 816.891.6599
Email: sfakc@shinnfuamerica.com



CANADA -
Shinn Fu Company of Canada, Inc.
2840 Argentia Road, Unit 9
Mississauga, Ontario L5N 8G4
Canada
Tel: +1.905.820.3737
Fax: +1.905.820.1166
Email: sales@shinnfucanada.ca



AUSTRALIA -
Shinn Fu Australia Pty.Ltd.
15 Viewtech Place
Rowville 3178 Victoria
Australia
Tel: 61.3.9755.8277
Fax: +61.3.9755.8219
Email: sales@shinnfaustralia.com



ASIA -
Shinn Fu Corporation Headquarters
7F., NO.618 Ruei Guang Road
Nei Hu District, Taipei City 114
Taiwan R.O.C.
Tel: 886.2.87517888
Fax: 886.2.87517999
Email: managment@shinnfu.com



JAPAN -
Shinn Fu Japan Co., Ltd.
O's 520 ATC bldg. 2-1-10 Nanko Kita,
Suminoe-Ku, Osaka 559-0034
Japan
Tel: +81.06.6614.9714
Fax: +81.06.6.6614.9711
Email: sales@sfjapan.com



EUROPE -
Shinn Fu Europe B.V.
Tussenrimer 20, 4704 SR Roosendaal
The Netherlands
Tel: +31.165.583.300
Fax: +31.165.583.310
Email: sales@sfeu.nl